#### CONGRATULATIONS ON YOUR CAR COVER SELECTION

Manufactured with a unique 4-layer non-woven polypropylene construction of a rugged Spun Bond outer layer attached to two melt blown (moisture barrier) middle layers and joined with a softer inner layer to produce a water resistant fabric that pampers and protects.

This investment will prolong the life of your vehicles exterior and interior by protecting the paint, trim, weather-stripping, dashboard, upholstery, carpeting. These breathable covers repel water, but won't trap moisture as they protect your vehicle finish from sun, dirt, droppings, and other airborne pollutants that harm the paint – they are great indoors or out.

Your cover is manufactured to the highest quality standards. It has been specially treated to be water repellent and mildew proof while retaining the all-important "Breathing Quality" necessary for superior car paint protection. This breathing fabric separates our "Water Repellent" cover from other "Water Proof" covers which may trap moisture and cause paint and vinyl; top damage. Do not be alarmed if moisture collects between the cover and the vehicle surface. The diamond bond pattern allows air and humidity to escape preventing paint deterioration from trapped air and moisture. The non-woven fibers are naturally water resistant and will shed water under normal conditions — in extended rainstorms even the best fabrics will absorb varying amounts of moisture, but the 4-layer cover dries easily as it allows air to circulate thru the fibers.

COVER USE: (Warning – Do not use cover on a vehicle that has been painted in the past 12 months! Pant continues to cure for up to 1 year and the off-gas from the paint can be trapped beneath the cover and damage the paint.)

Depending on the vehicle, many cover patterns have a similar front and rear profile. An identifying "front" label is sewn into the bottom elastic seam at the cover front.

# **EASY FOLDING INSTRUCTIONS:**

Always fold and roll in the same direction. Step (1) removal of the cover, (2) fold sides up toward center of car from nose. (3) roll cover to the rear. For your convenience this cover has already been rolled for easy installation. To install - simply reverse the folding procedure, starting at rear, unroll the cover over the top (to the front) of the vehicle and unfold over the sides.

# NON-RETRACTABLE ANTENNA:

If your vehicle is equipped with a non-retractable antenna, it will be necessary to provide an opening cover. This can be done by centering the main seams of the cover on this vehicle, mark the location and appropriate spot. Heat a pointed object (smoldering iron or wood burning elements are ideal), melt the correct size hole being careful to seal all edges completely to avoid places where tears begin.

#### THEFT DETERRENT:

Optional cable lock – Protect your investment with a "Lock Kit" which includes plastic coated cable and hardened pad lock.

## **WASHING INSTRUCTIONS:**

This cover is made of a strong, durable polypropylene fabric which resists common stains, soil, mildew and rot. Light brushing with a soft brush will remove most dirt. Mud can usually be rinsed out. The fabric does not require harsh scrubbing to clean soiled arear.

## FOR PERSISTENT SOILING:

- 1. Wet soiled fabric area with water
- 2. Wash area with a mild, non-detergent soap such as Ivory soap. Work into a lather with sponge. Light work the lather into the soiled areas.
- 3. Rinse thoroughly with large amounts of water to remove residual soap. Residual soap can cause fabric leakage.
- 4. Air-dry completely, a minimum of 6-8 hours.

  NOTE: While the fabric is soapy, water will pass through. Rinse thoroughly and let dry completely to restore water repellency. Air drying is recommended. Machine wash or other high temperature drying methods will damage the fabric.